



Solar
Green. Smart. Durable

Solar LED Batten



Features:

- Designed Linear sleek Aesthetic PVC housing
- High efficiency LED's for optimum light output and savings in power.
- High quality PC cover for LED linear lamp ensures soft and glare free lighting
- Short circuit and surge protection for enhanced reliability and longer service life of driver
- Wide beam angle of 120° with efficacy over >95 Lm/W.

Product Dimensions



Wattage	'L' Length	'W' Width	'H' Height
5W	290mm	23mm	33mm
9W	578mm	23mm	33mm
12W	578mm	23mm	33mm
18W	1150mm	23mm	33mm

Product Descriptions	Lumen (lm)	In. Current (mA)	CRI	CCT
Solar LED Batten 5W	450 lm	410mA	≥80	5500-6500K
Solar LED Batten 9W	850 lm	750mA	≥80	5500-6500K
Solar LED Batten 12W	1160 lm	1000mA	≥80	5500-6500K
Solar LED Batten 18W	1740 lm	1500mA	≥80	5500-6500K



HPL Electric & Power Ltd

Corp. Office : Windsor Business Park, B-1D, Sector-10,
Noida, U.P. - 201301, INDIA. | Tel.: +91-120-4656300
Registered Office : 1/21, Asaf Ali Road, New Delhi - 110 002, INDIA.
E-mail : solar@hplindia.com; hpl@hplindia.com

Customer Care No. :
18004190198

www.hplindia.com