

Branch Offices:

AHMEDABAD

B-802, Iscon Elegance,
Nr. Prahalad Nagar Corner,
Opp. Karnavati Club,
S.G. Highway- 380 051
Ph.: 079 - 66168835, 66168836
Fax : 079-66168837
E-mail: ahmedabad@hplindia.com

BANGALORE

No.2D, IInd Floor, Farah Winsford,
133, Infantry Road, Bangalore - 560 001
Ph.: 080-22863068 Telefax : 080-22863069
E-mail: bangalore@hplindia.com

BHUBANESWAR

N3-135, IRC Village, Nayabali,
Behind Old Sai Baba Temple,
Bhubaneswar-751 012
Ph.: 0674-6538229 Telefax : 0674-2550826
E-mail: orissa@hplindia.com

CHANDIGARH

Plot No. 57, 5th Floor
Industrial & Business Park, Phase-1
Chandigarh - 160002 Ph.: 0172-2639157
E-mail : chandigarh@hplindia.com

CHENNAI

"Amar Sindur" S-4, 2nd Floor,
No.-43, Pantheon Road, Egmore,
Chennai-600 008
Ph.: 044-28551530, 28551537
Fax : 044-42638243
E-mail: chennai@hplindia.com

COCHIN

2nd Floor, A.K.S. Mahal Building,
XL/7813J, Achutha Warriar Lane,
M.G.Road,Ernakulam,Cochin-682 035
Telefax : 0484-2354595
E-mail: cochin@hplindia.com

COIMBATORE

Designer Complex,
Door No.130, C /2, 2nd Floor,
Dr. Nanjappa Road, Coimbatore - 641018
Ph.:0422-4393995
E-mail : coimbatore@hplindia.com

DEHRADUN

R/09/4/6, 1st Floor, East Canal Road,
Dehradun-248001
Ph.: 0135-2710567, 2710587
E-mail: Uttranchal@hplindia.com

GUWAHATI

Rajgarh Road, Opposite China Town
Restaurant Guwahati - 781 003
Ph.: 0361-2450889
E-mail: guwahati@hplindia.com

HUBLI

9-10, 1st Floor, Vernekar Plaza,
Desh Pande Nagar, Hubli-580029
Ph.: 0836-4251463
E-mail : hubli@hplindia.com

HYDERABAD

No. 7-1-58, flat No.403, 4th Floor,
Concourse Building, Green
Lands Road, Hyderabad - 500 016
Ph.: 040-23740567,66687878,66773117
Telefax: 040-40035959
E-mail: hyderabad@hplindia.com

INDORE

203, Millinda Manor 2 RNT Marg,
Near Ravindra Natya Grah,
Indore- 452 001, Ph.: 0731-4280525
E-mail: Indore@hplindia.com

JAIPUR

512, 5th floor, Plot No. 8-9,
Corporate Park, Gopal Badi,
Ajmer Road Jaipur - 302 001
Ph. : 0141-4021035, 4018426
E-Mail: jaipur@hplindia.com

JAMMU

Plot No.86 Yard No.6
Transport Nagar, Jammu- 180006
E-mail: jammu@hplindia.com

KANPUR

17/14, 2nd Floor, Opposite Nanarao Park,
The Mall, Kanpur - 208 001 (U.P.)
Ph.: 0512-2316017 Telefax: 0512-2353743
E-mail: kanpur@hplindia.com

KOLKATA

69, Ganesh Chandra Avenue, India House
7th Floor, Block-C, Kolkata - 700 013
Ph.: 033-65394379 Fax :033-22252716
E-Mail: calcutta@hplindia.com

LUCKNOW

1st Floor, Jain Building, 14/A5,
Park Road Hazratganj ,Lucknow
Ph.: 0522-4021687
E-Mail: lucknow@hplindia.com

LUDHIANA

698 - D, Model Town, Extn.,
Opp. silverstone Hotel, Ludhiana-141 003
Ph. : 0161-5000877
E-Mail : ludhiana@hplindia.com

MUMBAI

2H, Rushabh Chambers 2nd Floor,
Off-Makwana Road, Near Rubi Hotel Marol
Andheri East Mumbai - 400 059
Ph.: 022-61830810-20 Telefax: 022-28528181
E-mail: mumbai@hplindia.com

NAGPUR

Jagtap House, Plot No. 07,
1st Floor, Ganesh Gruh Nirman Society,
Near Ganesh Mandir, Ring Road,
Pratap Nagar, Nagpur - 440022,
Ph.: 0712-2222988
E-mail: nagpur@hplindia.com

PATNA

Hem Plaza, 5th Floor - 510
Fraser Road, Patna - 800001(Bihar)
Ph. : 09308070166
E-mail: patna@hplindia.com

PUNE

Sunrise Skyline 3rd Floor,
Plot No. 28/2 Scheme No. 11 B
Opp. MSEB Office Somwar Peth
Pune - 411 001 Ph. : 020-69200902
E-mail: pune@hplindia.com

RAIPUR

1st Floor, Near Holy Heart School
Chattisgarh College Road, Civil Line,
Raipur (C.G.)-492 006 Ph.:0771-6541590
E-mail : raipur@hplindia.com

RANCHI

203, Mahalaxmi Complex, Line Tank
Road, 2nd Floor Ranchi - 834 001
Telefax : 0651-2206144
E-mail : ranchi@hplindia.com

SILIGURI

Parasuna Bhawan, Ward No.13,
Udham Singh Sarani, Asram Para,
Siliguri-734001

VADODARA

409/410, Silver Oak Complex,
Near Sainik Park Char Rasta,
Productivity Road, Akota,
Vadodara - 390020 Gujarat
Ph.: 0265-2341747 Fax:0265-2352107
E-mail : baroda@hplindia.com

VIJAYAWADA

D.No.-29-37-135, 2nd Floor,
G. R. Plaza, Eluru Road,
Beside Canara Bank, Vijayawada-520 002
Ph.: 0866-662291
E-mail : vijayawada@hplindia.com

VIZAG

B.K. Towers, 49-34-1/63, 3rd Floor
Akka Yyapalem Main Road, NH-5 Junction,
Vizag-530 016 (A.P.)
Ph.: 0891-2794506, 6461730
Fax:0891-2743531
E-mail : vizag@hplindia.com

Resident Offices:

Agartala	Balasure	Davangere	Jharsuguda	Moradabad	Silchar	Vapi
Agra	Belgaum	Durg	Jodhpur	Mysore	Surat	Varanasi
Allahabad	Berhampur	Goa	Kanyakumari	Nagercoil	Sholapur	Vellore
Anantpuram	Bhilai	Gorakhpur	Kolhapur	Nasik	Srinagar	
Aurangabad	Bhopal	Gulbarga	Kota	Patiala	Sambalpur	
Amravati	Bilaspur	Jabalpur	Madurai	Pondicherry	Tirupati	
Akola	Bijapur	Jabli	Malda	Rajkot	Trichy	
Angul	Calicut	Jamshedpur	Mangalore	Rourkela	Trivandrum	
Bareilly	Cuttack	Jalandhar	Meerut	Salem	Udaipur	

HPL Electric & Power Ltd.

Corp. Office : Windsor Business Park, B-1D, Sector-10,
Noida, U.P. - 201301, INDIA. | Tel.: +91-120-4656300
Registered Office : 1/21, Asaf Ali Road, New Delhi - 110 002, INDIA.
E-mail : hpl@hplindia.com; enquiry@hplindia.com

Customer Care No. :
18004190198

www.hplindia.com



Product Profile 2017



Switchgear | Metering | LED Lighting | Protection | Wire & Cable | Modular Switch

About **HPL**

HPL's vision of creating a niche, as a major player in India Electrical Industry with commitment to state-of-the-art technology & world class products.

HPL Group possess 6 most modern manufacturing units, ISO 9001 : 2000; ISO 14001; OHSAS 18001 certified located at Gurgaon, Kundli, Sonapat, Panipat, New Delhi and Himachal Pradesh having 5,00,000 sq. feet covered area to manufacture products confirming to International and India standards.

HPL Products Profile has the following Strategic Business Units :

- LV Switchgears
- LV Protection Devices
- Metering and Energy Management Systems
- Lighting
- Luminaires
- Wires & Cables
- Electrical Wiring Accessories

HPL Products are tested at CPRI, ERDA, ERTL, NPL etc. according to Indian Standards, whereas MCB's Rewireable Switches & Electronic Energy Meters carry ISI marking. Further HPL products have approvals from CPWD state PWD's, MES, BSNL & many more Institutional users.

HPL Group with Head Office at New Delhi has extensive Sales & Marketing Network of 90 Branch offices & Representative Offices, over 2400 Authorised Dealers and 18000 Retailers across country, who are committed to provide solutions and services to customer's delight. HPL is also exporting its products to Middle East, SAARC and European Countries.



Contents

METERS

Page
1-9

- Panel Meters • Power Factor Controller • Electronic Energy Meter
- Prepaid Meter • Digital Multifunction Panel Meters • Din Rail Meter
- Smart Meter

INDUSTRIAL PRODUCTS

Page
10-14

- Air Circuit Breaker • MCCB • MCCB DB • Contactor & Relays
- AV Changeover Switches • LBS & SDF • Fuse Switches

DOMESTIC PRODUCTS

Page
15-19

- Bsafe - MCB, DB, RCCB & RCBO • ACCL
- Techno - MCB, DB & RCCB • Rakshak - MCB & DB

LED LIGHTING & LUMINAIRES

Page
20-30

- LED Lamps • Mini & Full Retrofit • Retrofit & Non Retrofit CFL
- Consumer / Commercial / Industrial / Outdoor Lighting / HID Lamps

WIRES CABLES

Page
31-33

- Domestic & Industrial Wire • Networking Cable • Instrumentation cable
- Control Cable • Speciality Cable • Submersible Cable

Electrical Wiring Accessories

Page
34-35

- smART - Modular Switches • Socket • Controllers • Speciality Products
- Elmo Switch • Smarter - Accessories • TUFF Solo Switches



emfis - Digital Multi-Function Meter

Salient Features

- -/5A in class 0.5 & 1.0 accuracy
- Suitable for 3 Phase 4 Wire LT Network.
- CT Primary Programming upto 6000A (For direct reading)
- Three line LCD backlit display.
- Displays: Voltage, Current, Frequency, Power Factor, Power, & Trivector Energy.
- Three push buttons on the front panel for programming and scrolling.
- Maximum demand in kVA / kW with integration Period of 30 Minutes (Optional)
- RS485 Communication (Optional)

emfis HT - Digital Multi-Function Meter

Salient Features

- Programmable CT secondary for 5A & 1A
- Suitable for HT 3Phase 3 Wire /3 phase 4 wire (different model) application
- Display in Scroll Mode: Active Energy kWh, Apparent Energy kVAh, Reactive Energy kVAh, Phase to Phase voltage, Instantaneous, Average, Maximum and total Current, Active Power kW, Reactive Power kVAR and Apparent Power kVA, Total Instantaneous Power Factor, Frequency
- RS485 Communication (Optional)



emfis - vif Digital Multi-Function Meter

Salient Features

- -/5A in class accuracy 1.0
- Suitable for 3 Phase 4 Wire LT Network
- CT Primary Programmable upto 6000A
- Backlit LCD Display 17 parameters including: Phase to Phase voltage, Phase to Neutral Voltage, Instantaneous Current, Average Current, Maximum Current, Total Current, Frequency



emfis - vie Digital Multi-Function Meter

Salient Features

- Three Line Backlit LCD Display
- Optically Isolated Energy Pulse Output
- RS485 MODBUS Communication
- Provision for Special Screens Shots
- CT Secondary -/1A for -/5A (site selectable)
- Additional Parameters Power On Hour / Run Hours



emfis - vifp Digital Multi-Function Meter

Salient Features

- -/5A in accuracy class 1.0
- Suitable for 3 Phase 4 Wire LT Network
- CT Primary Programmable upto 6000A
- Three Line Backlit LCD display.
- Measures & Displays 39 parameters including : Phase to Phase Voltage, Phase to Neutral Voltage, Instantaneous, Average, Maximum and Total Current, Active Power kW, Reactive Power kVA and Apparent Power kVA, Instantaneous and Total Power Factor, Frequency

emfis vifpe - Digital Multi-Function Meter

Salient Features

- -/5A in accuracy class 1.0
- Suitable for 3 Phase 4 Wire LT Network
- CT Primary Programmable upto 6000A
- Three Line Backlit LCD display.
- Measures & Displays 40 Parameters including : Active Energy, Phase to Phase Voltage, Phase to Neutral Voltage, Instantaneous, Average, Maximum and Total Current, Active Power kW, Reactive Power kVAR and Apparent Power kVA, Instantaneous and Total Power Factor, Frequency
- RS 485 Communication (Optional)



emfis - Plus Digital Multi-Function Meter

Salient Features

- Suitable for 3 Phase 4 Wire LT Network.
- Three line LCD backlit display.
- Displays: Voltage, Current, Power Factor, Power, Trivector Energy & THD.
- Last 6 month history parameters for kWh, kVAh, kVAh (lag, lead) & MD KW, kVA through Communication
- Relay Output for V, I, Total kW, Total kVA, F, kW MD & kVA MD.
- Last 30 days Load Survey through communication.
- Last 10 Occ. / Res. event for each relay 1 & 2 through communication



emfis - DC Digital Multi-Function Meter

Salient Features

- Displays : Voltage, Current, Power, Energy
- RS485 MODBUS RTU Communication (Optional)
- Password Protected Programming
- Backlit LCD type Display (16 X 2 line Dot Matrix)
- 6 Months History for kWh, MD kW, Channel Peak Load available on communication
- Reverse Shunt Connection Indication
- Reverse Voltage Connection Indication
- Shunt Disconnection Indication





Dual Source Meter

Salient Features

- One Meter records Active Energy of two different sources : Mains & Generator
- Backlit LCD display
- Suitable for 3 Phase 4 Wire Network
- Accuracy class 0.5 & 1.0
- Rs485 MODBUS communication (optional)

Dual Source Plus

Salient Features

- One meter records Active Energy of Two Sources
- Measures over 45 Parameters including Voltage, Current, Frequency, kW, kVA; kVA_r, PF, Active Energy for Mains, Generator and Total, MD in kW and kVA for Mains and Generator separately with date and time, Run Hours, Power on Hours
- Relay outputs for V, I, kW, kVA, F, kW Demand, kVA demand
- Last 6 months history parameters for kWh and MD through communication
- Last 10 event logging for Mains/ Generator switching



3Phase Panel Mounted Meter with LCD Display (CT 2E)

Salient Features

- CT Operated, -/5A in class 1.0 accuracy
- CT Primary programmable upto 6000A (For Direct reading)
- No separate Auxiliary supply required
- Low Power Consumption less than 1 watt per phase
- Pulse Output
- Anti tamper features



3Phase Panel Mounted Meter with LCD Display (CT 2EA)

Salient Features

- Backlit LCD display.
- CT operated -/5A in class 1.0 accuracy.
- RS 485 communication
- CT Primary programmable upto 6000A (For direct reading).
- Pulse output.



3Phase Panel Mounted Meter with Counter Display (CT2M)

Salient Features

- CT Operated, -/5A in class 1.0 accuracy
- Available upto 800/5A (for direct reading) (Ref. Catalogue for available CT Ratio)
- No separate Auxiliary supply required
- Low Power Consumption less than 1 watt per phase
- Pulse Output
- Anti tamper features



êbrit : Single & Three Phase Ammeter

Salient Features

- Push button based site programming of CT Ratio
- Bright 4 Digit 14mm LED display
- Colour indication for R, Y & B phases
- Universal Auxiliary Supply : 80 to 300V AC/DC
- Same model for A & kA
- Auto scroll facility & scroll lock facility (For Three Phase meter)



êbrit : Single & Three Phase Voltmeter

Salient Features

- Push button based site programming of PT Ratio
- Network selection for Star (3 Phases 4 wire) and Delta (3phase 3 wire)
- Bright 4 Digit 14mm LED display
- Colour indication for R, Y & B phases
- Universal Auxiliary Supply : 80 to 300V AC/DC
- Same model for V & kV
- Auto scroll facility & scroll lock facility (For Three Phase meter)



êbrit : PF Meter

Salient Features

- Measurement range Zero Log Unity-Zero Lead
- Accuracy $\pm 0.01\%$
- Lag / Lead indication on the display
- Bright 4 Digit 14mm LED display
- Universal Auxiliary Supply - 80 to 300V AC/DC



êbrit : Kilo Watt Meter

Salient Features

- Push button based site programming of CT & PT ratio.
- Available in accuracy class 1.0 & 0.5 (Maintained through out the measurement range.
- Measure range 0-3.000kW (Direct Measurement)
- Bright 4 Digit 14mm LED display.
- Universal Auxiliary Supply - 80 to 300V AC/DC.



êbrit : Frequency Meter

Salient Features

- Measurement range 40.00 - 99.99 Hz.
- Accuracy Class 0.2 (Maintained through out the measurement range.)
- Bright 4 Digit 14mm LED display.
- Universal Auxiliary Supply - 80 to 300V AC/DC.



êbrit : Power Meter

Salient Features

- Common Meter for kW, kVA and kVAR
- User selectable measurement of kW/ kVAR/ kVA
- Available in Class 0.5 & 1.0
- Sustained accuracy through out the range
- Universal auxiliary supply – 80 to 300 V AC/DC
- Push Button based site programming of CT Ratio
- Bright 4 Digit 14mm LED Display



êbrit : Multi Meter

Salient Features

- Three line LED Display multifunction energy meter
- CT secondary -/1A or -/5A (site selectable)
- Password protected programming
- RS 485 MODBUS communication
- Provision for special screens display
- Measurement Range- 60V AC to 300V AC P-N
- Pulse output



êbrit : Advance Meter

Salient Features

- Voltage & current harmonic (upto 51st)
- CT secondary -/1A or -/5A (site selectable)
- THD (%) phase wise phase - neutral voltage (Volt)
- THD (%) phase wise current (Amp)
- THD (%) line voltage (Volt)
- RS485 Modbus Communication



HPL - Power Factor Controller

Salient Features

- Microprocessor based intelligent auto switching control.
- Automatic C/K and rated step adjustment.
- Automatic CT polarity correction.
- Display of power factor, current & total harmonic distortion of current.
- Programmable sensitivity.
- Last step can be used as alarm / fan output.
- Under / Over voltage alarm, compensate alarm & high harmonic distortion alarm.



Trivector Meter

Salient Features

- Range : LT-CT operated -/5A
CT/PT operated -/5A & -/1A for HT application
- Accuracy class 0.5 as per IS 14697 / CBIP 88 / IEC.
- Logging & display for tamper data.
- Measurement & recording of Trivector energy
- Communication : Optical & Hardwired RS232
- TOD, load Survey data, tamper information downloadable to CMRI through optical port.



Three Phase Dual Source Energy Meter

Salient Features

- One meter records Active Energy of two source
- Optical port communication & RS485 MODBUS communication
- Mains / Generator selection through 240V AC / 24V DC Sensing
- Indication for current reversal tampering and phase availability on the LCD itself
- Indication on display to indicate the source in use
- Load survey / Tamper logging available
- Ratings available : -/5A CT Operated 10-60A



3Phase Electronic Energy Meter with LCD Display (Available with & without optical comm. port)

Salient Features

- Accuracy Class 1.0 as per Is13779
- ISI marked ratings: -/5A CT operated 5-20A, 10-40A, 10-60A
- All standard anti tamper features provided

Optional Features

- Optical communication port
- Logging and display of tamper data
- TOD, load survey, tamper information downloadable to CMRI through optical port
- Display in absence of power supply
- Suitable for AMR



Din Rail Mounting Meters

Salient Features

- Current rating single phase 5-30A, three phase 10-60A & 20-80A & -/5A
- Communication Modbus RTU for three phase & pulse output for single phase
- Programmable CT ratio and Scroll lock
- Suitable of dual source application (only three phase)





3Phase Electronic Energy Meter Counter Type Display



Salient Features

- Range 5-20A, 10-60A, -/5A Ct operated in class 1.0 accuracy as per IS 13779.
- Meter records correct energy with same accuracy under reverse current connection.
- LED indication for current reversal tampering provided.
- Phase available indication provided
- Anti tamper features.

Single Phase Electronic Energy Meter with LCD Display (Available with & without optical comm. port)

Salient Features

- Accuracy Class 1.0 as per IS13779
- ISI marked ratings: -/5A CT operated 5-20A, 5-30A, 10-60A
- All standard anti tamper features provided

Optional Features

- Optical communication port / Rs232 Port
- TOD, load survey, tamper information downloadable to
- CMRI through optical port
- Display in absence of power supply



Single Phase Electronic Energy Meter Counter Type Display



Salient Features

- Range 5-20A, 5-30, 10-40A, 10-60A, CT operated in class 1.0 accuracy as per IS 13779.
- Tamper indications provided.
- Phase available indication provided.
- Anti tamper features.

Net Meter for Solar Roof Top & Solar Plant Application

Salient Features

- Available in Single phase & Three phase Net Metering
- Range: 5-30A, 10-40A, 10-60A, HT CT/LT CT, -/5A
- 4 quadrant meter with pulse output LED's for kWh & kVAh
- As per IS 13779 & IS 14697
- Separate readings for Active Energy kWh, kVAh Import & Export
- Net Energy kWh, kVAh with sign



ABT Meter (Availability Based Tariff)



Salient Features

- As per IS-14697 & IEC 62053 accuracy Class 0.2 and 0.5
- Four-quadrant metering for export & import
- DLMS/COSEM open protocol support
- Up to 8 tariffs per day
- Up to 12 channel of load profile data and block load profile data

Smart Meter

Salient Features

- Robust and Sleek design
- Variant: Single phase & Three phase
- Communication: Two way, Open protocol (DLMS), GSM/RF
- Internal relay for Remote Load disconnect/ Reconnect
- Anti tamper and fraud detection
- Security - Password protected user login and parameter settings
- Online data downloading through GSM/GPRS communication.



Prepaid Metering Solutions



Salient Features

- Available in Single Phase & Three Phase.
- Ratings available 10-60A in class accuracy 1.0
- As per IS 15884:2010.
- Also available in dual source application
- Transparent system for utility and consumers.
- No manual meter reading, No bill delivery system.
- Supply disconnection is automatic for non payment customer

LPR Zigbee Metering Solutions

Salient Features

- Available in Single Phase 5-30A, 10-40A & 10-60A
- Available in 3 phase 10-40A & 10-60A
- Energy Meter Based on IEEE 802.15.4
- Automated device address management
- Each meter aids transfer of data for self as well as neighboring meter
- Wire less commissioning, network scalability features





Long Range Integrated CT Meter

Salient Features

- No need of external CT, meter box and accessories
- Wide current range, 40-200A
- Thread-through meter- cable passes through meter
- Communication options-
 - Optical Port
 - Inbuilt GSM/GPRS Modem
- Scheduled data transfer on demand

Automatic Meter Reading Solution

Salient Features

- High speed GSM/ GPRS communication 4800/9600 bps
- For remote metering application



Transparent Pilfer Proof Meter Box

Salient Features

- Made of UV stabilized transparent polycarbonate/Flame retardant high grade engineering plastic.
- Unique arrangement for pilfer proof interlocking with hinge type boxes.
- Complying to IS:14772 and tested at CIPET.
- Sealable optical port provision on the cover of the meter box.

Air Circuit Breaker



intelliPROTECT

Salient Features

- Range : 630A – 6300A
- Operational voltage upto 690V & even above - on request
- Icu 50kA to 120kA at 500Vac
- Ics = 100% Icu throughout the range
- Icw : 50kA to 100kA (for 1 sec)
- Customer oriented Trip Relay - with advanced measurement functions & communication functions
- Tested & certified as per IS/IEC 60947-2

intelliSMART

Salient Features

- Range 630A - 2000A & Icu 50kA, 3P & 4P, Icw 50kA for 1 sec. at 500Vac. Fixed Type and Draw Out Type.
- LSIG Protection with Microprocessor at variable time delay
- Digital display of current and voltage parameters
- Short circuit protection starts from 131 %



Moulded Case Circuit Breaker



TAB™ : Thermal Adjustable Breaker

Salient Features

- Conforms to IS/IEC 60947-2.
- Available in 1P, 2P, 3P & 4P Versions rated current from 20A-800A & breaking capacity (from 10kA to 65kA).
- 4P version available with neutral fully protected.
- Adjustability-offers close protection to different load condition.
- Line load reversibility, Low let through energy.
- Wide range of internal and external accessories.
- ROHS Compliant, also available for DC application.
- Single Pole MCCBs are available from 10A-250A with breaking capacity from 10kA-50kA, SP MCCBs from 63A-250A are available with thermal adjustable feature

Motor Duty MCCBs (MD Series)

Salient Features

- Available upto 22 kW / 30 HP in two frame.
- Breaking capacity - 25kA / 36kA.
- Clear indication of ON, OFF & Trip position.
- Low let through energy.
- For Special motor starting condition (Starting time beyond 10 Sec & other specific condition) - please contact us.





Microprocessor MCCB

Salient Features

- Rated 25A-800A Breaking capacity 25kA/36kA/50kA/65kA.
- No of Poles 3/4.
- Overload protection ADJUSTABLE in the range 30% to 100% of In with variable time setting.
- Short circuit Protection ADJUSTABLE in the range 400% to 1000% of Ir with variable time setting.
- Ground Fault Protection ADJUSTABLE in the range 10% to 40% of In with variable time setting.
- Communication Feature available.
- Suitable for DISCRIMINATION.
- NO EXTERNAL Power required for the electronic circuit.
- True RMS sensing for precise and RELIABLE protection.

MCCB Distribution Panel

Salient Features

- Range : 4, 6, 8, 10 & 12 ways
- Incoming – Upto 630A, Outgoing – Upto 250A
- No. of poles of MCCB – 3 / 4
- Multifunction Digital Metering - Optional
- Shrouded bus bar can withstand high fault currents
- Provision for single Door / Double Door



MCCB Enclosure

Salient Features

- MCCB conform to IS/IEC 60947-2
- Current ratings from 16A - 800A, 3P & 4P version
- Low let through energy
- Breaking Capacity (kA) : 10kA - 65kA (with MCCB)
- Line Load Reversibility
- Minimum maintenance, User friendly, robust & compact
- Highly reliable tested solution



Contactors & O/L Relays

Thermal Overload Relays

Salient Features

- Differential Bimetallic overload relays from 0.1 to 800A
- Built in 1NO+1NC potential free contacts
- Choice of Contactor or separate Mounting
- Option of Manual / Auto or Remote Reset
- Sealable cover to avoid tampering, Trip indicator
- Class 10A or Class 20
- Site Mounted add on accessories



Contactors

Salient Features

- Widest Range of 3P & 4P Contactors upto 800A
- Control Contactor with option upto 12 contacts
- Capacitor Duty Contactors upto 62 kvar
- Highest Electrical Life upto 2.5 million operations
- Site mounted add on accessories (Auxiliary Contacts, Mechanical Interlock, Surge Suppressor, Timer, Mechanical Latch Units)
- Type II Co-ordination
- CE marked & UL Certified

Motor Protection Circuit Breaker (Motocop)

Salient Features

- Wide range of MPCB from 0.1 to 80A
- 22 Ratings in just 2 frames
- Rotary Type Operation (Direct & Extended Handle)
- Protection against O/L, S/C & Single Phasing
- Higher Breaking capacity upto 50kA, 480 VAC
- Electrical / Mechanical Life - 1 Million Operations
- Suitable for Isolation & Type II Co-ordination
- Ambient Temperature Compensated
- Site Mounted add on accessories



Submersible Pump Correction Pump

Salient Features

- Range-1HP to 40HP (DOL & Star Delta) in 2 Models
- Heavy Duty Contactors for longer life.
- Control Voltage- Phase (130 to 290V) or 3 Phase (280 to 440V).
- Short Circuit Protection - MCB/MCCB (10kA) in Deluxe Model.
- Other Protections - Single Phasing / Over Load / Unbalance Voltages / Reversal of Phases.
- Auto - Manual Bypass Switch.
- Ammeter & Voltmeter with Selector Switch.
- LED indications for R, Y, B Phases & Pump ON/OFF.



AV Changeover Switch

HPL AV Onload Changeover Switch

Salient Features

- Range: 6 frame sizes, 63- 3150A, 4 Pole, IS 13947 part 3/93
- Arc Chute plates to enhance contact life. 100% Neutral.
- Compact body of fiber glass, reinforced polyester resin.
- High Mechanical & Electrical life.
- Total safety with Terminal cover, Source Separator and Phase Barrier as standard feature.
- Mounting possible in both horizontal and vertical position.
- Available in Open Execution and Sheet Steel enclosures.
- Prewired Auxiliary contacts upto 2NO NC.





new



AV ATS

Salient Features

- Range 125A-630A, 4P, AC 23A, 3 frame sizes
- Trip Safety as standard feature, CE marked, RoHS Compliant
- Power monitoring- kWh, kVAh, kVA, kVArh
- User selectable RS232 & RS485 communications
- Remote monitoring
- Configurable over riding voltage parameters
- Maximum spares for on site repair solutions
- Auto DG Start/Stop
- Configurable Digital Inputs and Outputs

HPL - AV Switch Fuse Changeover

Salient Features

- Range : 125A-630A, 4 Pole, 415V AC as per IS 13947 Part 3/93.
- Arc Chute plates to enhance contact life. 100% Neutral.
- Body of fiber glass reinforced polyester resin.
- Prewired Auxiliary contacts upto 2NO NC.
- Protection against over current and short circuit faults by fuses of high rupturing capacity of 80kA rms.
- Total safety with Terminal cover, Source Separator and Phase Barrier as standard feature.
- Available in Open Execution / Sheet Steel enclosure.



HPL- AV On Load Bypass Switch

Salient Features

- Range: 125A - 1600A, 4 Pole, 415 V AC as per IS 13947 Part 3/93.
- Arc Chute plates to enhance contact life. 100% Neutral.
- Switch is designed for specific need in IT industries where UPS and Servo stabilizer provides main source of supply.
- Prewired Auxiliary contacts upto 2NO NC.
- Available in Open Execution / Sheet Steel enclosure
- Total safety with Terminal cover, Source Separator and Phase Barrier as standard feature.



HPL - AV Cubicle Load Break Switch

Salient Features


- Range : 63 - 3150A, 4 Pole, 415 V AC as per IS 13947 Part 3/93.
- Arc Chute plates to enhance contact life. 100% Neutral.
- Prewired Auxiliary contacts upto 2NO NC.
- Suitable for DC-23A, 260V, application without any derating.
- Available in Open Execution / Sheet Steel enclosure.
- Total safety with Terminal Cover, and Phase Barrier as standard feature.



LBS & SDF



CML-9100012591



LK - HPL Switch Disconnecter Fuse


Salient Features

- Range : 32A to 800A, TP, TPN & 4 Pole, 415V, 50Hz
- Confirms to latest IS 13947-3 / IEC 947-3
- Tested at CPRI, Bhopal for AC-23A duty
- Multiple Roller Contact Mechanism for long life and better performance
- Available in open execution and sheet steel enclosure
- Available in BS & DIN type HRC fuse links
- Excellent performance for capacitor duty applications also


LK - HPL Load Break Switch (Isolator)

Salient Features

- Range : 32A -3150 TP, TPN & FP, 415V 50Hz
- Confirms to IS 13947-3
- Multiple roller contact mechanism for long life & better performance
- Available in open execution & sheet steel enclosure
- Excellent performance for capacitor duty applications also



Fuse Switches



CML-9100011387

HRC Fuse Link & Base-BS & DIN Type

Salient Features

- Range (DIN type - Fuse Link & Base) : 2 Amps to 630 Amps
- Range (BS Type Fuse Holder) : 20A to 125A
- Breaking capacity >80kA at 415V, AC, 50 Hz
- Front & Busbar Connection options for fuse Holders (of BS type).
- Conforms to IS : 13703 / 93 & IEC 269-1986
- Low Watt loss
- Tested at CPRI Bhopal

HPL - LT Switchgear

Salient Features

- Range: Rewireable Switch Fuse Unit : 16 Amps to 320 Amps
- Fuse Switch Unit : 63 Amps to 800 Amps
- Changeover Switches : 16 Amps to 2000 Amps
- HPL Porcelain Fuse : 16 Amps to 320 Amps
- Tested at CPRI Bhopal, IIT Kanpur, NTH Calcutta
- Confirms to IS 13947-3 / IS 2086



CML-9100011387



bsäfe MCB

Salient Features

- Range : 0.5Amp - 63Amp in SP, SPN, DP, TP, TPN, FP
- Specification : IS/IEC-60898-1
- Rated Voltage : 240/415V AC, 50Hz
- Rated Breaking capacity 10kA & Energy Limit Class 3
- Installation and removal of MCB without removing Busbar, as 3 position mounting clip makes it possible
- Bi-connect termination on both sides & snap fitting on accessories
- Padlock/Sealing facility : Contact position indicator red/green
- Cable termination capacity of wire upto 35sq. mm.
- Can be sealed with leads in the ON or OFF position

bsäfe Distribution Board

Salient Features

- Available in SPN and TPN versions
- Compact and aesthetically designed to meet the requirement of high end customer
- Intelligently designed to provide the maximum space for wiring of Db's
- Mounting of MCB's on Height adjustable DIN Channel
- Available with Cement Guard Protection



bsäfe RCCB

Salient Features

- Range: 25-80Amp, 2 Pole & 4 Pole Version
- Sensitivity: 30mA, 100mA, 300mA
- Conforms to IEC / EN: 61008 & IS:12640
- Dedicated earth leakage protection
- Voltage Rating 240/415V (AC), 50Hz
- Protection against Electrocution, Short Circuit & Electrical fire
- Consistent performance, Compact & Space saving
- Auxiliary Switch optional

bsäfe RCBO

Salient Features

- Range 6Amp-63Amp, 240/415V AC
- Available in SP+N, 2P(4 Mod.), 4P(8 Mod.)
- Rated Residual Current 30mA, 100mA, 300 mA
- Rated Short Circuit Capacity 10kA
- Design Add on type in DP & FP
- Specification Reference IS12640-2 & IEC 61009-1



Techno MCB

Salient Features


- Range : 0.5 to 63 Amps 240/415V, AC
- Available in SP, SPN, DP, TP, TPN & FP
- Breaking capacity 10kA
- Insulation voltage : 660V, frequency : 50/60Hz
- Finger Touch proof (IP20)
- Mid Trip Technology
- Protection against Short Circuit & Over Load
- Low let through energy & low watt loss
- Energy limit class 3
- Trip free mechanism
- Available in B, C & D Curve
- Accessories :UV, Shunt trip, Auxiliary contact
- DC MCB available in SP & DP
- DC MCB voltage : 12V to 220V



Techno Isolator

Salient Features

- Range : 40, 63, 80, 100 & 125 Amps
- Conforms to IS/IEC 60947-3
- Available in 2P, 3P & 4P version
- Finger touch proof (IP-20)



Techno RCCB

Salient Features

- Range: 25-80Amp, 2 Pole & 4 Pole Version
- Sensitivity: 30mA, 100mA, 300mA
- Conforms to IEC / EN: 61008 & IS:12640
- Dedicated earth leakage protection
- Voltage Rating 240/415V (AC), 50Hz
- Protection against Electrocution, Short Circuit & Electrical fire
- Consistent performance, Compact & Space saving
- Auxiliary Switch optional

Techno MCB Changeover Switch

Salient Features

- Range : 25A, 40A & 63A
- Conforms to IS/IEC 60947-3
- Choice of 2 Pole & 4 Pole versions
- Voltage Rating 240 / 415V (AC), 50Hz
- Front Operation with three stable positions I-O-II
- Isolator at middle position
- DIN Rail Mounting





Automatic Changeover with Current Limiter (ACCL) Single Phase



Salient Features

- Range : 0.6Amp - 10Amp in SPN
- Specification : IEC - 60947-6-1
- Rated Voltage : 240V AC, 50Hz
- Microcontroller based DIN rail mountable with neutral Isolation
- Inbuilt SMPS for low power consumption
- Operational status indication through LED
- Automatic generator on/off facility
- Built-in time delay for fail safe changeover

Automatic Changeover with Current Limiter (ACCL) Three Phase

Salient Features

- Range : 25A, 40A & 63A
- Specification IEC 60947-6
- Voltage 415V AC
- Electronic & Mechanical interlock for safe changeover
- Built in time delay for fail safe changeover
- Overload tripping in DG supply
- Wide Voltage operation - (140 to 280) volts
- Reliable micro controller based design for sensing & control



Rakshak MCB

Salient Features

- Range: 6 to 63A
- Available in SP, SPN, DP, TP, TPN & FP
- ISI marked & conforms to IS:60898-1
- Protection against Short Circuit & Over Load
- Finger Touch proof (IP20)
- Available B & C curve
- Breaking Capacity : 6kA
- Voltage Rating : 240/415V
- Low watts loss hence energy saving
- Low let through energy



Rakshak Isolator

Salient Features

- Range : 40 & 63Amps
- Conforms to IS 13947-3
- Available in 2P, 3P & 4P Version
- Finger touch proof (IP20)



Distribution Systems Single Door



Salient Features

- User friendly, Aesthetically designed available in **EX series** Distribution Systems in 4ways to 16 ways
- SPN & TPN Versions
- Fitted with DIN channel, Bus Bar, Neutral Link Bar, Earth Bar, Inter connecting cables with copper thimble
- Can be mounted on surface / flush

Distribution System Double Door

Salient Features

- User friendly, Aesthetically designed available in **DX series** Distribution Systems in 4 ways to 16 ways
- SPN & TPN Versions in Single / Double Door
- DB's available with cement guard
- Bus Bar rating upto 200Amp of tinned copper, fully insulated
- Fitted with DIN channel, Bus Bar, Neutral Link Bar, Earth Bar, Inter connecting cables with copper thimble
- Complete range of DB's with Double punched knockout to facilitate different size cable glands
- TPN DB's fitted with detachable gland plates
- Double Door DB's in Surface / flush mounted design
- Special DB's for projects also available



Vertical Distribution Systems

Salient Features

- Aesthetically designed, good looking & superior DB's with latest style
- Fitted with Bus Bar, Shorting Links, Neutral Bar & Earth Bar
- Compact design having complete shrouding all over the inter connecting links
- Provision of ELCB along with TPN/FP Isolator as incomer
- Suitable to use as SP/DP/TP/TPN outgoing
- Available with MCCB as incomer



Tier DB

Salient Features

- Aesthetically and user friendly design available in Single / Double / Three / Four Row version
- Provide total flexibility as per site needs
- Configuration as per customer choice of Incomer and Outgoing
- Top and bottom, removable gland plates with knockouts
- Compatible for Flush/ Surface mounting





Phase Selector Distribution Systems



Salient Features

- Compact distribution system
- Convenient mounting and operation
- Flexibility to use MCB's and RCCB/RCBO
- Fitted with : DIN channel Bus Bar Neutral Link Bar 3 Nos
- Phase changeover switches duly wired (except for MCB's and RCCB's)

Pre-wired Distribution Board

Salient Features

- DB's Duly pre-wired with FR/FRLS wire
- Available SPN & TPN Versions
- Fitted with bus bar terminal block for incoming/outgoing phase
- Neutral & earthing duly pre-wired
- Provision of MCB / Isolator / RCCB as incoming Single phase outing
- Available in 1.6mm & 1.2mm sheet steel thickness



Consumer Unit - Double Door

Salient Features

- Aesthetically designed Single phase distribution systems
- Painted with the latest powder coating technology for long lasting surface finish
- Available with transparent plastic cover



Plug & Socket Distribution Systems

Salient Features

- Range : SP-10-20A
 : TP-20-30A
- Provision for SP / SPN / DP / TP MCB
- CRCA powder coated DB
- Elegant Surface / Flush Mounting Design



LED GLO 3W, 5W, 7W & 9W



Salient Features

- High efficiency Led's for optimum light output and savings in power.
- Aesthetically designed heat sinks with specially designed fins.
- High quality diffuser for glare free distribution.
- Drivers with on board circuit protections.
- Highly efficient metal core PCB.

LED GLO 12W, 15W, 18W & 20W

Salient Features

- SMD LED's for good quality illumination and longer life
- Casted Aluminium heat sinks with specially designed fins
- High quality diffuser for glare free distribution
- Constant current drivers.
- Highly efficient metal core PCB.



LED GLO 30W, 40W & 50W

Salient Features

- SMD LED's for good quality illumination and longer life
- Casted Aluminium heat sinks with specially designed fins
- High quality diffuser for glare free distribution
- Constant current drivers.
- Highly efficient metal core PCB.



Decor Ball

Salient Features

- B22 & E27 base
- Available in color Red, Green, Yellow, Blue & Frosted
- Range in 1W in Ball & 0.5W in Candle
- Ideal for general lighting
- Flicker free, Instant Start
- Life upto 25000 burning hours.





Consumer Lighting

Bright



Salient Features

- Engineered & designed Linear sleek Asthetic PVC housing
- High efficiency Led's for optimum light output and savings in power .
- High quality PC cover for LED linear lamp ensures soft and glare free lighting
- Short circuit and surge protection for enhanced reliability and longer service life of driver
- Wide beam angle of 120° with efficacy over 100 Lm/W.

Phoenix Plus

Salient Features

- Engineered & designed Linear sleek Asthetic PVC housing
- High efficiency Led's for optimum light output and savings in power .
- High quality PC cover for LED linear lamp ensures soft and glare free lighting
- Short circuit and surge protection for enhanced reliability and longer service life of driver
- Wide beam angle of 120° with efficacy over 100 Lm/W.



Lumino

Salient Features

- Solid sate high brightness SMD LED's for good quality illumination and longer life.
- Excellent heat dissipation through high purity, high thermal conductivity heat sink.
- Special reflector system with high efficiency Translucence diffuser.
- Wide beam angle of 120° with efficacy over 80 Lm/W.



ONYX Plus LED

Salient Features

- Available in 6W, 12W, 15W & 18W
- High quality aluminum diecast housing
- Color Temperature 6500K/4000K/2700K
- Short Circuit & Open Circuit Protection On Driver.
- Highly Efficient Constant Current LED Drivers
- Diffused Light With Acrylic diffuser.



Phoenix Supreme



Salient Features

- High efficiency Led's for optimum light output and savings in power .
- Short circuit and surge protection for enhanced reliability and longer service life of driver.
- Replacement of 36W/40W Tube Light.
- Sleek & Compact Metal Batten for maximum light spread.

Phoenix Plus 20W

Salient Features

- Engineered & designed Linear sleek Asthetic PVC housing
- High efficiency Led's for optimum light output and savings in power .
- High quality PC cover for LED linear lamp ensures soft and glare free lighting
- Short circuit and surge protection for enhanced reliability and longer service life of driver
- Wide beam angle of 120° with efficacy over 100 Lm/W.



Lumino Plus

Salient Features

- Engineered & designed Linear sleek Asthetic PVC housing
- High efficiency Led's for optimum light output and savings in power .
- Recess Mounted, Compact Vertical.
- Suitable for low ceiling heights.





Regular Retrofit (T4)



Salient Features

- Compact lamp with inbuilt electronic control gear
- Single ended with B22nd & E27 bases
- Available in colours 6500, 4000 & 2700°K
- Range in 11W, 15W, 20W, 23W, 25W, 27W, 30W & 35W
- Ideal replacement for normal GLS bulb
- Flicker free instant start
- Six times more life than the normal GLS bulb
- High luminous efficacy and excellent colour rendering

Spiral Retrofit (T4)

Salient Features

- Compact lamp with inbuilt electronic control gear
- Excellent light distribution
- Single ended with B22nd & E27 bases
- Available in colours 6500, 4000 & 2700°K
- Range in 15W, 20W, 23W, 27W, 30W & 35W
- Ideal replacement for normal GLS Bulb
- Flicker free instant start
- Six times more life than the normal GLS Bulb
- High luminous efficacy and excellent colour rendering



Higher Wattage Regular/Spiral Retrofit(T5)

Salient Features

- High Power Factor > 0.9.
- Compact lamp with inbuilt electronic control gear.
- Single ended four tube, with B22d, E27 & E40 bases.
- Available in colours 6500, 4000 & 2700°K.
- Range in 45W, 65W & 85W (in both 4U & Spiral).
- Flicker free instant start.
- Six times more life than the normal GLS bulb.
- High luminous efficacy and excellent colour rendering.



Commercial & Institutional Lighting



Jupiter Plus 2W (CW/WW/B/R)



Salient Features

- Optics through designed lens offering medium beam distribution.
- Well designed housing including Aluminum heat sink.
- Separate replaceable electronic driver.
- Wide operating voltage range from 100 V–285 V.

Sleek Plus (Recessed Type)

Salient Features

- Range: 3W/6W/12W/15W & 18W
- Solid state high brightness SMD LED's for good quality illumination and longer life .
- Back lit illumination technology
- Excellent heat dissipation through high purity, high thermal conductivity heat sink .
- Special reflector system with high efficiency Translucence diffuser.
- On board short circuit and surge protections for reliable electrical system
- Wide beam angle of 120° with efficacy over 80Lm/ W .



Jonex Plus (Surface Type)

Salient Features

- Range: 6W/12W/15W & 18W
- Flat profile with wide-angle diffuser
- Housing made up of high heating conductive pure aluminum material
- Available in all color temperatures 6500 K/4000 K/2700 K
- Highly efficient constant current drivers with additional protections
- Instant light with low running temperatures
- Surface mounting application



LED Panel Lighting

Salient Features

- Solid state high brightness SMD LED's for good quality illumination and longer life .
- Back lit illumination technology
- Excellent heat dissipation through high purity , high thermal conductivity heat sink .
- Special reflector system with high efficiency Translucence diffuser.
- On board short circuit and surge protections for reliable electrical system
- Wide beam angle of 120° with efficacy over 90Lm/ W.
- Size 1'x1', 2'x2', 1'x2', 1'x4'
- Wattage: 18W, 30W & 36W





Lipto

Salient Features

- Available voltage in 1W & 3W.
- Recessed mounted round /square spot down lighter.
- COB based LED spot light specially designed into Aluminum housing.
- Suitable for all kind of Hotels, Showrooms & Residential sector.

Polic

Salient Features

- Available voltage in 6W, 9W, 12W, 15W, 18W & 24W.
- Recessed mounted COB based LED down lighter.
- Ideal for Hospitality sector of low to high ceiling.
- Housing made of Aluminum die cast for fast heat dissipation & longer life.



Bulk Head

Salient Features

- Available in 10W
- Made of pc housing
- Glare free in white color housing
- IP-65



Zoom COB LED

Salient Features

- Simple and easy integrative structure design, easy in installation
- Housing made up of high heating conductive pure aluminum material
- High quality COB chip with uniform colour temperature , high lumen efficacy and long life span
- Aesthetically designed reflector for optimum optics control
- Highly efficient constant current drivers with additional protections



Track Light & Solace COB LED

Salient Features

- COB based fully adjustable LED track light.
- 360° angle of rotation for LED track light.
- Aesthetically Designed high grade aluminum housing.
- High efficiency Led's for optimum light output and savings in power.
- Short circuit & surge protection for enhanced reliability and longer service life of driver.
- Separate replaceable electronic driver.
- Wide operating voltage range from 100V – 285V.
- Ideally suited for retail lighting with surface & recess applications.



Neptune Plus

Salient Features

- Available in 5W / 10W / 20W
- Replacement of T-8/T-5 fittings.
- High efficiency LED's for optimum light output and savings in power .
- High quality PC Diffuser for LED linear lamp ensures soft and glare free lighting
- Specially designed aluminum housing for excellent Heat dissipation .
- Short circuit and surge protection for enhanced reliability and longer service life of driver
- Wide beam angle of 120° with efficacy over 100 Lm/W.



Neptune Gold

Salient Features

- Available in 5W / 9W / 18W
- Replacement of T-8/T-5 fittings.
- High efficiency LED's for optimum light output and savings in power .
- High quality PC Diffuser for LED linear lamp ensures soft and glare free lighting
- Specially designed PC body for excellent Heat dissipation.
- Short circuit and surge protection for enhanced reliability and longer service life of driver
- Wide beam angle of 120° with efficacy over 100 Lm/W.



Indus LED Tube (T8/T5 Retrofit Solution)

Salient Features

- Available in 2ft. & 4ft. Sizes.
- High efficient LED's for optimum light output and savings in power.
- High quality PC diffuser for LED linear lamp ensures soft and glare free lighting.
- Specially designed aluminium housing for excellent Heat dissipation.
- Short circuit and surge protection for enhanced reliability and longer service life of driver
- Wide beam angle of 120° with efficacy over 100 Lm/W.



LED PLL Lamp 9W / 18W

Salient Features

- Available in 9W & 18W
- Replacement of T-8/T-5 fittings.
- High efficiency LED's for optimum light output and savings in power .
- High quality PC Diffuser for LED linear lamp ensures soft and glare free lighting
- Specially designed PC body for excellent Heat dissipation.
- Short circuit and surge protection for enhanced reliability and longer service life of driver
- Wide beam angle of 120° with efficacy over 80 Lm/W.





LED Legacy PC

Salient Features

- Single Tube & Double Tube Option
- High quality PC cover for LED linear lamp ensures soft and glare free lighting
- Specially designed housing for excellent Heat dissipation
- Aesthetically designed box type industrial fixture
- Industrial Batten suitable for use with single or twin LED Tube
- CRCA Sheet steel powder coated housing in white to improve resistance against corrosion

LED Strom PC

Salient Features

- Available in Single Tube & Double Tube option.
- Made up of corrosion resistant unbreakable poly carbonate body.
- High quality PC cover for LED linear lamp ensures soft and glare free lighting.
- Weather Proof IP-65.
- Suitable for Industrial Purpose.
- Surface & Suspended mounting.




Industrial Luminaries

LED Highbay

Salient Features

- Range: 70W/90W/100W/120W/150W/180W.
- Highly efficient heat sink designed to ensure prolong the life span of the LED.
- Efficiently designed constant current driver with wide range input voltage 140V to 285V.
- Significantly lower running cost as compared to conventional fixtures.
- Available with toughened glass.
- IP-65.



Well Glass IP-65

Salient Features

- Range: 30W & 40W.
- Integral radial fins on housing for effective heat dissipation.
- High power, high efficiency LED chip.
- White powder coated internal reflector.
- Thermally isolated driver and optical compartment.
- Specially designed for IP65 protection.
- Loop in Loop out facility.



Outdoor Lighting



LED Street Light

Salient Features

- Available wattages - 15W to 90W
- LED efficacy -> 130 lumen / watt
- Lamp life - 50,000 burning hours with L 70 criteria
- CRI > 70, PF > 0.95, THD < 10%
- Confirms LM 79 & LM 80
- Special Features : Reverse EMI protection provided / over voltage protection upto 300V / surge protection upto 6kV.

LED Street Light

Salient Features

- Available wattages - 120W to 200W
- LED efficacy -> 130 lumen / watt
- Lamp life - 50,000 burning hours with L 70 criteria
- CRI > 70, PF > 0.95, THD < 10%
- Confirms LM 79 & LM 80
- Special Features : Reverse EMI protection provided / over voltage protection upto 300V / surge protection upto 6kV.



LED Flood Light

Salient Features

- Available wattages - 15W to 150W
- LED efficacy -> 130 lumen / watt
- Lamp life - 50,000 burning hours with L 70 criteria
- CRI > 70, PF > 0.95, THD < 10%
- Confirms LM 79 & LM 80
- Special Feature : Reverse EMI protection provided / over voltage protection upto 300V / surge protection upto 6kV.



LED Flood Light

Salient Features

- Available wattages - 200W to 350W
- LED efficacy -> 130 lumen / watt
- Lamp life - 50,000 burning hours with L 70 criteria
- CRI > 70, PF > 0.95, THD < 10%
- Confirms LM 79 & LM 80
- Special Features : Reverse EMI protection provided / over voltage protection upto 300V / surge protection upto 6kV.



Flood Light

Salient Features

- Available in 2x250W & 2x400W MH/SV lamp.
- Pressure die cast Al LM-6.
- Tempered protective toughened glass.
- Confirms IP-65/66
- Applications : High Mast, Stadiums & Industrial Area etc.





Flood Light

Salient Features

- Available in 70W, 150W, 250W & 400W MH/SV lamp.
- Pressure die cast Al LM-6.
- Tempered protective toughened glass.
- Confirms IP-65.
- Application : Construction site, Industrial Area & Parks etc.

LED Post Top Lanterns

Salient Features

- Available wattages - 9W to 40W
- LED Options - LED lamp / Discrete Versions
- Lamp life – 50,000 burning hours with L 70 criteria
- CRI > 75
- Confirms LM 79
- Application : Gardens, Pathways, Societies etc.



LED Bollard

Salient Features

- Available wattages - 5W to 12W
- LED Options - LED lamp
- Lamp life – 50,000 burning hours with L 70 criteria
- CRI > 75
- Confirms LM 79
- Application : Gardens, Societies, Petrol Stations, Malls, Driveways etc.



CCMS

Salient Features

- User Friendly
- Single Point Control System Fully Programmable
- Automatic Report Generation
- Periodic Data Download at Pre Set Intervals.
- Controlling & Monitoring In Groups as Well as Up To Individual Light Point
- Programmable Automatic Real Time Operation Of Street Lights With Sunset & Sunrise Time.
- Dimming At Off Peak Hours possible



LED Ground Burials & Spike Lights

Salient Features

- Available wattages - 3W to 15W (12W for Spike)
- LED efficacy - upto 130W
- Lamp life - 50,000 burning hours with L70 criteria
- CRI > 75
- Confirms - IP65 (IP66 available on request)
- Application : Driveways, Facade Lighting, Ambient Lighting etc.



Metal Halide Lamps

MH lamps are available in Double Ended & Single Ended versions. Double ended lamps are available in 70w & 150w. Single Ended lamps are available in Elliptical (ranging from 70w to 400w) & Tubular version (ranging from 35w to 400w). These lamps offers efficacy upto 80-85 lumens / watt.

G12 Single Ended, 35, 70, 150W

Salient Features

- UV Shield
- Longer Life
- Precise optical control
- Better Colour Rendering
- Highly Efficient



Double Ended, 70, 150W

Salient Features

- UV Shield
- Longer Life
- Precise optical control
- Re-strike
- Better Colour Rendering
- Highly Efficient
- Faster Warm up & Hot



Single Ended-Elliptical, 70, 150, 250, 400W

Salient Features

- UV Shield
- Better Cold Starting
- Faster Warmup & Hot
- Better Colour Rendering
- Superior Lumen Maintenance
- Re-strike



Single Ended-Tubular, 70, 150, 250, 400W

Salient Features

- UV Shield
- Better Cold Starting
- Faster Warmup & Hot
- Better Colour Rendering
- Superior Lumen Maintenance
- Re-strike



Accessories

Salient Features

- Electromagnetic Ballast (Copper wound open construction ballast) The VPIT Magnetic Ballasts are available for Compact Fluorescent Lamps (CFL) ranging from 9W to 36W Fluorescent Tubular Lamp (FTL) ranging from 18W to 40W High pressure Sodium vapor lamp/metal Halide Lamp range from 70W to 400W.
- Electronic Ballast are available for CFL ranging from 9W to 36W & FTL ranging from 18W to 36W.





Domestic & Industrial Wire


Salient Features

- Range : 0.5 to 400 Sq. mm in Single Core & Multicore
- Available in FR / FRLS / HR / ZHFR insulation Conforms to IS : 694
- Multi strand 100% Pure annealed Electrolytic grade copper conductor
- Bunching of copper in uniform lay & diameter
- High insulation Resistance
- Double Insulated with ultra thin layer

Co-axial Cable /CCS

Salient Features


- Range : RG-59, RG-6, RG-11
- Solid bare annealed electrolytic grade copper
- PE foam
- Aluminum Alloy Braiding / Aluminum Foiling / Taping
- Specially formulated FR PVC
- Low attenuation, High band width Moisture proof, low loss signal Quality.



Submersible Cable

Salient Features


- Range : 1.0 to 50.0 Sq. mm three core flat cable.
- Stranded bare annealed electrolytic grade copper conductor.
- Specially formulated PVC compound (Type A & ST-1).
- Round submersible cable can be specially asked for.
- Conforms to IS:694.



Telephone Cable

Salient Features

- Range : 0.40 & 0.50mm dia conductors available up to 50 pairs.
- Solid / Stranded Bare annealed copper Conductor.
- PVC / PE Insulated.
- Individual / Overall Shielded with Aluminium tape (Polyester backed)/ Melinex Tape / Wire braiding / Aluminium foil taping.
- Low cross talk, Low attenuation, High speed transmission.



Control Cable

Salient Features

- Range : 1.5 & 2.5 Sq. mm upto 37 Core, 1100 Volt Grade confirming to IS: 1554-1/1988 & IS 7098-1/1988.
- Solid/ Stranded 100% pure annealed Electrolytic copper conductor.
- Insulation PVC/XLPE/HR
- Armourd/ Unarmourd- GI Round wire/Flat Strip.
- Outer Sheath PVC (ST-1 & ST-2)/FRLS/FR/ ZHFR.
- Heavy Duty Performance.
- Best combination safety.
- Efficient & economical .
- Use in Process Control, Communication and Panel control.



Instrumentation Cable

Salient Features

- Range : 0.5 Sq. mm to 2.5 Sq. mm Conforming BS 5308-I & II
- Shielding: Core/Pair/Triad/Quads.
- ABC/ATC, Solid/Standard 100% pure annealed Electrolytic grade copper conductor.
- Armourd / Unarmoured - GI Round wire / Flat Strip.
- Low attenuation and cross talk.
- For Analog & Digital Signals.
- Low structural return loss.
- Use in Digital Control, measuring & Communication systems.



Networking Data Cable (CAT - 5e & 6)

Salient Features

- Range : 4-Pair UTP CAT-5e and CAT-6 Cable.
- Solid 100% pure annealed Electrolytic grade copper conductor.
- Low attenuation and cross talk.
- Low structural return loss.
- Frequency 100MHz for CAT-5e cable and 250MHz for CAT-6 Cable.
- Gigabite Ethernet
- Suitable for Voice, Data, Video.
- 100 ohm impedance cable.



Fire Survival Cables

Salient Features

- Range : 0.5 Sq. mm to 2.5 Sq. mm Conforming BS: 7846 600/1000 Volts
- Shielding: Core/Pair/Triad/Quads with Mica/glass fire barrier tape.
- ABC/ATC, Solid/Standard 100% pure annealed Electrolytic grade copper conductor.
- Armourd / Unarmoured - GI Round wire / Flat Strip.
- Operating Temperature -10°C +90° C.
- Fire Tests Bs6387 CWZ, BS 8491, IEC 60331- 2.





Flat Elevator Cables



Salient Features

- Range : 0.5 to 1.5 Sq. mm. for upto 12 core.
- Flexible bare annealed electrolytic grade copper.
- PVC insulated & PVC sheathed.
- Specially formulated PVC.

DC Solar Cable

Salient Features


- Range : Single core 2.5, 4, 6, 10, 16 & 25 Sq. mm.
- Flexible tinned annealed electrolytic grade copper conductor.
- Specially formulated cross linked Polyolefin compound insulated and low smoke zero halogen sheathed with UV and Ozone resistant.
- Latest requirement for PV system as per TUV spec number to 2 pfg-1169/08.2007.



CCTV Cables

Salient Features

- Range : 3+1 CCTV and 4+1 CCTV Cable.
- Coaxial Cable consists of solid annealed bare copper conductor.
- PE insulated with Nylon foamed dielectric aluminum foil taped, Jelly flooded, braided with aluminum alloy / copper and FR PVC sheathed cable.
- Low loss characteristics reduced attenuation of the video signal.



Modular Switch

6A/10A/20A/32A- DP switch



Salient Features

- ROHS Compliance
- Captive Screws
- Dual Protection for spark shield
- High Grade Flame Retardant Engineering Plastic
- Silver Nickel contacts for trouble free operations

AC Box 3M & 4M

Salient Features

AC Box 3M
Protection for short circuit and overload.

MCB : 25 Amp
Socket : 25 Amp
Top : 25 Amp

AC Box 4M
Protection for short circuit and overload.

Motor Starter : 25 Amp
Socket : 25 Amp
Top : 25 Amp



Elmo Switch

Salient Features

- Complies with IS 3854:1997
- Tested upto 1 Lakh operations
- Silver Alloy Contact
- Shrouded terminals
- Front loading & removing
- High Grade Flame Retardant Engineering Plastic



Tuff (Solo Switch)

Salient Features

- High Grade Flame Retardant Engineering Plastic
- Tested upto 2 lakh operations
- 10 Years Warranty





Smarters Accessories



Spike Guard

Salient Features

- Universal sockets
- Length of cable 1.6-1.8 Mtr
- Surge protection in built
- Overload protection in built with resetting switch
- Metal Oxide Varistor (MOV) used as safeguard against surge & spikes
- Material in use - FR ABS plastic
- Connector swivels 3600

Extension Cord

Salient Features

- Equipped with universal socket & 2 pin sockets
- Rated current - 6A
- Rated Voltage - 240V AC, 2.4KW
- PVC insulated wire 4mts. in length
- Engineering plasti material for high impact & chemical resistance
- Material in use - FR ABS plastic



Remote Bells

Salient Features

- Plug in type / battery operated wireless bell with volume adjustment.
- 32-48 polyphonic sounds to choose
- Transmitter with IP44 protection
- Volume setting in the receiver
- Operating range up to 80-260mtr. in opne area
- Auto learning code
- Available in different colours in specific models
- Rated voltage 110V-220V AC (Plug in type)
- Volume 50-80dB



Batten / Angel Holder

Salient Features

- Rated current - 2A
- Rated Voltage - 250V AC
- Ducts provided on outer surface for heat dissipation
- SS Spring provided for better flexibility & easy locking for bulb, CFL & LED Bulb
- Highly conductive brass terminals
- Material-FR polycarbonate UV stabilized



Plug Tops 6A/16A



Salient Features

- Rated Current 6A/16A
- Rated Voltage 240V AC
- 100% shock proof
- Highly conductive nickel plated contacts
- Material-FR polycarbonate UV stabilized

International Travel Adaptor

Salient Features

- Rated Current 6A
- Rated voltage 110V-240V AC
- MaterialEngineering plastic for high impact and chemical resistant
- Compatible to countries like Australia, China, USA, Europe & UK etc.
- Equipped with universal & USB sockets



Multi Plugs

Salient Features

- Equipped with universal socket & 2 pin sockets
- Universal multi socket for different types of plugs used around the world
- Rated current-10A
- Rated Voltage 240V AC
- Nickel plated brass contacts for better conductivity
- Available in 4 different transparent colours- Purple, Blue, Green & Orange
- Material-FR polycarbonate UV stabilized



Water Detector

Salient Features

- Sounding a loud alarm signal of exceeding 80dB at 10 feet
- Advance electronic accurate design to detect the water leakage
- Easy installation & maintenance
- Fully automatic operation
- Ergonomic design of detector casing
- Place anywhere

